



# GTX

Heavy Duty Construction,  
Highest Power Motors and  
Handmade in America  
Why Look Anywhere Else?



**DRAIN SAVER**  
KEEPS DEBRIS OUT  
OF DRAINS

**36 VOLT SYSTEM**  
RUNS FOR FULL  
SHIFT

**HEAVY DUTY  
CONSTRUCTION  
PREVENTS DAMAGE**

**2 TANK SYSTEM**  
EASILY DRAIN  
RECOVERY TANK

**ROLLERS (6" TALL)**  
PROTECTS WALLS  
AND KICK PLATES

**HD FRONT DRIVE**  
CLIMB RAMPS

**DISK OR CYLINDRICAL  
SCRUB DECK**



**FACTORYCAT**  
INDUSTRIAL CLEANING EQUIPMENT



Scan This QR  
Code With  
Your Phone  
For More  
Information

www.factorycat.com  
1 (800) 634-4060  
(+001)262-681-3583



## BODY CONSTRUCTION / DIMENSIONS

Tank Material:	Poly 3/8" (10 mm)
Chassis Construction:	3/16" Steel (5 mm) Powder Coated Steel
Front Wheel (Diameter x Width):	10" x 3" (25 x 8 cm) - Solid Black
Rear Wheels (Diameter x Width):	(2x) 12" x 5" ([2x] 31 x 13 cm) - Solid Black
Size (L x W x H):	54" x 26" x 55" (137 x 66 x 140 cm)
Weight (w/o Batteries):	755 - 805 lbs (343 - 365 kg)
Weight (w/ 245 ah Batteries):	1,195 - 1,245 lbs (542 - 565 kg)

## BRUSH / PAD SYSTEM

Disk Dimensions:	26" - (2x) 13" Diameter (66 - [2x] 33 cm)
34 Inch Deck Includes HD Side Doors	30" - (2x) 15" Diameter (76 - [2x] 38 cm)
	34" - (2x) 17" Diameter (86 - [2x] 43 cm)
Disk Motor:	(2x) 0.75 hp / 300 rpm ([2x] 559 watts)
Disk Brush Speed:	200 rpm
Cylindrical Dimensions:	24" - (2x) 5.25" x 22" (61 - [2x] 13 x 55.9 cm)
5.25" Diameter Brush	27" - (2x) 5.25" x 25" (69 - [2x] 13 x 64 cm)
34 Inch Deck Includes HD Side Doors	30" - (2x) 5.25" x 28" (76 - [2x] 13 x 71 cm)
	34" - (2x) 5.25" x 32" (86 - [2x] 13 x 81 cm)
Cylindrical Motor:	(2x) 0.75 hp / 350 rpm ([2x] 559 watts)
Cylindrical Brush Speed:	750 rpm
Actuator Rating:	500 lbs (227 kg)
Brush Pressure Settings:	(5) with Auto Adjust
Brush Down Pressure:	Up to 200 lbs (91 kg)

## POWER SYSTEM

System Voltage:	36 VDC
Standard Battery:	245 ah WET
Optional Battery:	325 ah WET / 360 ah WET / 250 ah AGM / 335 ah AGM
Run Time:	Up to 6.0 Hours*
*Run times are based on continuous scrubbing run times.	
Charger:	120VAC / 60 Hz Input - 36VDC / 25 amp Output

## DRIVE SYSTEM:

Power:	0.75hp - All Gear / Sealed (559 watts)
Forward Speed:	0 - 320 ft/min (4 mph)
	0 - 98 m/min (6 km/h)
Reverse Speed:	0 - 230 ft/min (3 mph)
	0 - 70 m/min (5 km/h)

## SOLUTION / RECOVERY SYSTEMS:

Solution Tank Capacity:	33 Gallons (125 liters) - w/ Graduated Site Tube
Solution Flow / Filter:	0 - 1.0 GPM / Stainless Inline (0 - 4 LPM)
Recovery Tank Capacity:	36 Gallons (136 liters) - 1.5" diameter Drain Hose
Demisting Chamber:	1.25 Gallons (5 liters)
Drain Saver:	30 cubic inches (492 cubic cm)
Vacuum Power:	1.0 hp / 3 Stage (740 watts)
Vacuum Specs (Water Lift / Airflow):	68" / 72 cfm (173 cm / 2 cm/m)
Squeegee:	26D - 32" Curved w/ 4-sided Rear Blade
	30D, 24C, 27C, 30C - 35" Curved w/ 4-sided Rear Blade
	34D, 34C - 38" Curved w/ 4-sided Rear Blade

## GENERAL:

Cleaning Width:	26", 30" & 34" - Disk (66, 76 & 86 cm)
	24", 27", 30", & 34" - Cylindrical (60, 69, 76, 86 cm)
Decibels:	67 dB
Productivity - Theoretical:	Up to 44,118 sqft (4,099 sqm)**
**Productivity is based off of ISSA 2010 Cleaning Times	
Productivity - Practical:	Up to 20,408 sqft (1,896 sqm)**
**Productivity is based off of ISSA 2010 Cleaning Times	
Seat with Switch Included	Headlights Included

Series Scrubber Specifications

# GTX

AUTHORIZED DISTRIBUTOR

# FACTORY CAT

www.factorycat.com  
 Phone: (800) 634-4060  
 International: (+001) 262-681-3583

© RPS Corporation 2016

All Rights Reserved

As our policy is one of constant improvement, all specifications are subject to change without notice.

(10/16) FC-GTX-SALESSHEET